

Safety Data Sheet

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System
Conforms to The United Nations Regulation Globally Harmonized System Revision 7
Date of Revision: 08/04/2018
Revision: 01

Section 1 - Chemical Product and Company Identification

1.1 Product Name: HP101

1.2 Synonym: Blend

1.3 VP Racing Fuels, Inc., 7124 Richter Road, Elmendorf, TX 78112, 210.635.7744

1.4 Recommended Use: Fuel

1.5 RESTRICTIONS on USE THIS FUEL IS FOR STREET DRIVEN MOTOR VEHICLE

1.6 Emergency Response Number: CHEMTREC 800-424-9300

International Emergency Telephone Number: +1-703-527-3887

1.7 See Section 16.3 for CHEMTRC in Country Emergency Numbers

Section 2 - Hazards Identification

2.1 GHS HAZARD

Hazard Classes Hazard Categories

Highly Flammable liquid/vapor Category 2 **Specific Target Organs toxicity single exposure** Category 3 **Specific Target Organs repeated exposure** Category 1 **Eve Irritation** Category 2B **Skin Irritation** Category 2 **Acute Toxicity (Oral)** Category 4 **Aspiration Hazard** Category 1 **Reproductive Toxicity** Category 1B **Toxic to Aquatic Life Long lasting effects** Category 2

2.2 Signal Word: Danger

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System Conforms to The United Nations Regulation Globally Harmonized System Revision 7



2.4 Hazard Statements

PHYSICAL HAZARDS: H225: Highly flammable liquid and vapor

HEALTH HAZARDS: H302: Harmful if swallowed

H304: May be fatal if swallowed and enters

airways

H315: Causes skin irritation

H319: Causes serious eye irritation

H336: May cause drowsiness or dizziness
H361: Suspected of damaging fertility or the

unborn child

H373: May causes damage to organs through

prolonged or repeated exposure

ENVIRONMENTAL HAZARDS: H411: Toxic to aquatic life with long lasting

effects

PRECAUTIONARY STATEMENTS: P102: Keep out of reach of children

P201: Obtain special instructions before use.

READ SDS BEFORE USE

P202: Do not handle until all safety precautions have

been read and understood

P210: Keep away from sparks and open flames-

No smoking

P240: Ground or bond container and

receiving equipment

P241: Use explosion-proof equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against

static discharge

P260: Do not breathe vapors

P264: Wash hands thoroughly after handling

P270: Do not eat, drink or smoke when using

this product

P271: Use only outdoors or in well ventilated

area

P273: Avoid release to the environment

P280: Wear protective gloves, clothing and eye

protection

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System Conforms to The United Nations Regulation Globally Harmonized System Revision 7

RESPONSE STATEMENTS:

STORAGE STATEMENTS:

DISPOSAL STATEMENTS:

P301 +P310+ P331: IF SWALLOWED: <u>USA</u> Immediately call the National POISON CENTER at 800-222-1222. <u>OUTSIDE USA</u> Immediately call poison center or doctor.DO NOT induce vomiting

P303+P361+P353: IF ON SKIN Take off immediately all contaminated clothing. Rinse skin with water

P304+P340: IF INHALED. Remove to fresh air and keep comfortable for breathing P305+ P338+P351: IF IN EYES rinse cautiously with water for at least 15 minutes. If present remove contact lenses if safe to do so and continue rinsing

P308+P313: If exposed or concerned get medical attention

P362+P363+P364: IF ON CLOTHING, take off contaminated clothing and wash it before reuse P313+P332+P337: If skin or eye irritation persists get medical attention

H314: Get medical attention if you feel unwell

P330: Rinse mouth

P370: In case of fire use foam, carbon dioxide, dry chemical to extinguish fire

P391 Collect spill

P405+P406: Store in a well-ventilated place, store locked up and keep cool

P501: Dispose of content and/or container in accordance with local, regional, national or international regulations

2.5 Hazards not otherwise classified (HNOC) or not covered by GHS: Repeated exposure may cause skin dryness or cracking

Section 3 - Composition / Information on Ingredients

3.1

CAS#	EC#	Chemical Names	Percent	Classification
N/A	N/A	Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	90-93%	None
64-17-5	200-578-6	1-Hydroxyethane		Flam. Liq. 2 H225, Eye Irrit. 2 H319

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System Conforms to The United Nations Regulation Globally Harmonized System Revision 7

3.2 Blend Contains

Chemical Names	CAS#	EC#	Classification	
2, 2, 4-Trimethylpentane	540-84-1	208-759-1	Flam. Liq. 1 H224, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 Central nervous Sys Inhalation H336, Aquatic Chronic 2 H411	
Phenylmethane	108-88-3	203-625-9	Flam. Liq. 2 H225, Asp. Tox. 1 H304, Skin Irrit. 2 H315, STOT SE 3 H336, Repr. 2 H361, STOT RE 2 H373	
1,1,2-Trimethylethane	78-78-4	201-142-8	Flam. Liq. 1 H224, Asp. Tox. 1 H304, Skin Irrit. 2 H315, Eye Irrit 2, H319, STOT SE 3 Central nervous Sys Inhalation H336, Aquatic Chronic 2 H411	

3.3 Trade Secret Provision and Chemical Concentration Disclosure: In accordance with OSHA and GHS Regulations we have withheld specific percentages of the chemicals in this mixture. The chemical concentrations have been disclosed as a blend and are applicable to the hazards as identified in this Safety Data Sheet.

Section 4 - First Aid Measures

4.1 Eye: Contact with the eyes can cause serious irritation. Symptoms may include discomfort or pain and redness. Severe overexposure can result in swelling of the conjunctiva along with tissue damage.

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

4.2 Skin: Prolonged and repeated liquid contact can cause defatting and drying of the skin and can lead to irritation and/or dermatitis.

Skin: Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid immediately. Wash clothing before reuse.

4.3 Ingestion: Liquid ingestion can cause inebriation, headache, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonia, pulmonary edema and even death.

Ingestion: Do NOT induce vomiting. Get medical aid immediately.

4.4 Inhalation: Prolonged breathing of high vapor concentrations can produce headache, dizziness, nausea, and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage and death resulting from respiratory failure.

Inhalation: Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult and **IF TRAINED**, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation without protection.

4.5 After first aid, get appropriate paramedic, or community medical support. The severity of outcome following an exposure may be more related to the time between the exposure and treatment, rather than the amount of the exposure. Therefore, there is a need for rapid treatment of any exposure.

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System Conforms to The United Nations Regulation Globally Harmonized System Revision 7

4.6 Note to Physicians: If you determine that a medical emergency exists and the specific chemical identity is necessary for emergency or first-aid treatment we will immediately disclose the specific chemical identity. Call CHEMTREC 800-424-9300 or 703-527-3887. We will require a written statement of need and confidentiality agreement, in accordance with OSHA's Trade Secret Regulations as soon as circumstances permit. In non-emergency situations, we will upon written request disclose a specific chemical identity.

Section 5 - Fire-Fighting Measures

- **5.1 General Fire Hazards:** Use water to cool containers exposed to fire
- 5.2 Hazardous Combustion Products: Avoid fumes of burning product.
- **5.3 Extinguishing Media:** Carbon dioxide, dry chemical, foam.
- **5.4** Fire Fighting Equipment/Instructions: Fire fighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Fire fighters should avoid inhaling any combustion products.

Section 6 - Accidental Release Measures

- **6.1 Spill /Leak Procedures:** Ventilate area highly flammable. Spillages of liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition away from the spill.
- **6.2** Spills: Avoid direct contact with material. Stop leak if without risk. Move containers from spill area. Prevent entry into sewers or waterways. Contain and collect spillage with non-combustible, absorbent material such as sand, earth, vermiculite or diatomaceous earth and place in a container for disposal.

Section 7 - Handling and Storage

- **7.1 Handling Precautions:** Wash hands and exposed skin thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid ingestion and contact with eyes, skin or clothing. Keep container tightly closed. Avoid inhalation.
- 7.2 Storage Requirements: Store in a tightly closed container in a cool, dry and well-ventilated area.

Section 8 - Exposure Controls / Personal Protection

8.1

Chemical Names	ACGIH- TLV	OSHA - PEL
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	20-300 ppm	20-300 ppm TWA
1-Hydroxyethane	1000 ppm TWA	1000 ppm TWA

8.2

ACGIH® = American Conference of Governmental Industrial Hygienists. TLV® = Threshold Limit Value. OSHA = US Occupational Safety and Health Administration. PEL = Permissible Exposure Limits. NOTE: TWA Means "TWA is the employee's average airborne exposure in any 8-hour work shift of a 40-hour work week which shall not be exceeded.

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System Conforms to The United Nations Regulation Globally Harmonized System Revision 7

- **8.3 Ventilation:** Provide general or local exhaust ventilation systems to maintain airborne concentrations below TLV/PELs Local exhaust ventilation are preferred because it prevents contaminant dispersion into the work area by controlling it at its source.
- **8.4 Contaminated Equipment:** Separate contaminated work clothes from street clothes and launder before reuse.

Remove this material from your shoes and clean personal protective equipment.

8.5 Personal protective equipment

8.5.1 Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

8.5.2 Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique to avoid skin contact with this product. Dispose of contaminated gloves after use. Select gloves tested to the ANSI/ISEA 105-2011 or European EN374 Standard.

Full contact: Viton Splash contact: Viton

Viton is a Registered Trademark of The DuPont Company

8.5.3 Eye protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

8.5.4 Skin and body protection

Impervious clothing flame retardant antistatic protective clothing, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

8.6 Protective Clothing Pictograms











Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System Conforms to The United Nations Regulation Globally Harmonized System Revision 7

Section 9 - Physical and Chemical Properties

9.1

Physical State: Liquid Appearance: Orange

Odor: Aromatic Hydrocarbon Odor Vapor Pressure: Not Available Vapor Density (Air=1): 3.9 Specific Gravity (H2O=1,): 0.73 Relative Density: Not Available Odor Threshold: Not Available

Flammability (solid, gas): Not applicable.

Evaporation rate: Not Available

Partition coefficient octanol/water: Not

Available

Water Solubility: Insoluble

Melting point/freezing point: Not Available Flash Point: 10°F (-12°C) close cup Boiling Point / Range: 208°F, (98°C) Lower Explosive Limits (vol % in air): 1% Upper Explosive Limits (vol % in air): 8%

Viscosity: 0.46 cSt 104°F,40°C

Auto ignition Temperature: Not Available **Decomposition temperature:** Not Available

pH: None

Section 10 - Stability and Reactivity

10.1 Stability: Stable under ordinary conditions of use and storage.

10.2 Polymerization: Hazardous polymerization has not been reported.

10.3 Chemical Incompatibilities: Strong oxidizing agents.

10.4 Hazardous Decomposition Products: Combustion produces carbon monoxide and carbon dioxide.

10.5 Conditions to Avoid: Avoid heat, sparks open flames and other ignition sources.

Section 11- Toxicological Information

11.1

Product Name	Results	Species	Dose	Exposure
Blend of Aliphatic and	Oral LD50	Rat	300-2000mg/kg	None Listed
Aromatic Hydrocarbons				
C-2 to C-20				
1-Hydroxyethane	Oral LD50	Rat	7060 mg/kg	None Listed

- **11.1.1** OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause Oral Toxicity.
- **11.2** Route of Entry: Inhalation, Ingestion, Absorption, Skin and/or Eye Contact
- **11.3 Aspiration Hazard:** European Chemical Agency Data Base shows that components of this product may be fatal if swallowed and enters airways.
- **11.4 Mutagenicity:** OECD Guideline Test results found in the European Chemical Agency Data Base show no components of this product to cause genetic defects

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System Conforms to The United Nations Regulation Globally Harmonized System Revision 7

- **11.5** Skin Corrosion/Irritation: OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause skin irritation. Repeated exposure may cause skin dryness or cracking.
- **11.6 Serious Eye Damage/Irritation:** OECD Guideline Test results found in the European Chemical Agency Data Base shows that components of this product to cause serious eye irritation.
- **11.7 Reproductive toxicity:** OECD Guideline Test results found in the European Chemical Agency Data Base show components of this product to cause damage to fertility or the unborn child.
- **11.8 Skin Sensitization** OECD Guideline Tests results found in the European Chemical Agency Data Base show no components of this product to cause skin sensitivity.
- **11.9 Respiratory Sensitization** OECD Guideline Tests results found in the European Chemical Agency Data Base show no components of this product to cause respiratory sensitivity.
- **11.10 Specific Target Organ Toxicity (Single Exposure):** European Chemical Agency Data Base shows that components of this product may cause damage to the central nervous system (CNS).
- **11.11 Specific Target Organ Toxicity (Repeated Exposure):** Contains chemicals which may cause damage to the following organs: kidneys, lungs, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).
- **11.12 Signs and Symptoms:** Effects due to exposure may include: Headache, Dizziness, Drowsiness, Metabolic Acidosis, Coma, Seizures. Symptoms may be delayed
- **11.13 Carcinogenicity:** OECD Guideline 453 Tests results found in the European Chemical Agency Data Base shows that no components of this product to cause cancer.

Chemical Name	IARC	ACGIH	NTP	OSHA
Blend of Aliphatic and Aroma Hydrocarbons C-2 to C-20		Not listed	Not classifiable as a carcinogenicity to humans	Not listed
1-Hydroxyethane	Not listed	Confirmed animal with unknown relevance to humans	Not listed	Not listed

Section 12 - Ecological Information

12.1

Product Name	Results	Species	Exposure
Blend of Aliphatic and Aromatic Hydrocarbons C-2 to C-20	Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the environment		
1-Hydroxyethane	LC50 8,140 mg/l	Fish	48 hours
1-Hydroxyethane	LC50 14,221 mg/l	Daphnia	48 hours

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System Conforms to The United Nations Regulation Globally Harmonized System Revision 7

Toxicity: OECD Guideline Test results found in the European Chemical Agency Data Base show components of this product to cause long-term toxicity to aquatic life.

12.2 Mobility: Floats on water

12.3 Persistence/degradability: Inconclusive technical data.

12.4 Bioaccumulation: Inconclusive technical data.

12.5 Other adverse effects: Inconclusive technical data.

Section 13 - Disposal Considerations

13.1 Disposal: DO NOT REUSE EMPTY CONTAINER! Container should be completely emptied prior to discard. Container with residues should be considered to be hazardous wastes. Contact a licensed contractor for detailed recommendations. Follow applicable federal, state, and local regulations.

Section 14 - Transport Information

14.1 US Transport Information





ID No.: UN 1203

Shipping Name: Gasoline

Hazard Class: 3
Packing Group: II
Label: Flammable
Placard: Flammable

Marking: MARINE POLLUTANT 2, 2, 4-Trimethylpentane when shipping ground greater than 119 gallons'

single container or any quantity by water

14.2 IMDG Transport Information







ID No.: UN 1203

Shipping Name: GASOLINE

Hazard Class: 3
Packing Group: II
Flash Point: (-40°C c.c.)
EmS Number: F-E, S-E
Label: Flammable
Placard: Flammable

Marking: Marine Pollutant 2, 2, 4-Trimethylpentane

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System Conforms to The United Nations Regulation Globally Harmonized System Revision 7

14.3 UN Dangerous Goods Transport Information



ID No.: UN 1203

Shipping Name: Gasoline

Hazard Class: 3
Packing Group: II
Label: Flammable
Placard: Flammable

Marking: Marine Pollutant 2, 2, 4-Trimethylpentane

Section 15 - Regulatory Information

15.1 US Regulations

US. Toxic Substances Control Act: All components of this product (VP 101 Street Legal) are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

TRI Reporting SARA 313: Phenylmethane

CERCLA Hazardous Substances and corresponding RQs: 2, 2, 4-Trimethylpentane 1000 pounds, Phenylmethane 1000 pounds

SARA Community Right-to-Know Program: All components of this blend.

Clean Water Act: Phenylmethane

Clean Air Act: 1,1,2-Trimethylethane

OSHA: All ingredients are regulated by 1910.1200

State Regulations
California prop. 65:



WARNING Reproductive Harm - www.P65Warnings.ca.gov."

Chemicals on the following State Right to Know Lists:

Massachusetts: All components of this product are on the Massachusetts Inventory or are exempt from Inventory requirements.

New Jersey All components of this product are on the New Jersey inventory or are exempt from Inventory requirements.

Pennsylvania: All components of this product are on the Pennsylvania Inventory or are exempt from Inventory requirements.

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System Conforms to The United Nations Regulation Globally Harmonized System Revision 7

15.2 International Regulations:

Australian Inventory of Chemical Substance: All components of this product are on the Inventory or are exempt from Inventory requirements

National Existing Chemical Inventory in Taiwan: All components of this product are on the Inventory or are exempt from Inventory requirements

Philippine Inventory of Chemicals and Chemical Substances All components of this product are on the Inventory or are exempt from Inventory requirements

China Existing Chemical Inventory: All components of this product) are on the Inventory or are exempt from Inventory requirements.

Section 16 - Other Information

16.1 Disclaimer: The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above is furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use.

16.2 References: References: CHEMpendium data base of Canadian Centre for Occupational Health and Safety (CCOHS), JJ Keller on Line, European Chemical Agency Data Base and MSDS and SDS of chemicals in this blend.

16.3 CHEMTREC in country emergency dial numbers:

CHEMTREC In-Country Dial Numbers	Local # Provided in Country	Toll Free in Country*	Greeting Language
	AMERICAS		
CHEMTREC Argentina (Buenos Aires)	+(54)-1159839431		Latin American Spanish
CHEMTREC Brazil (Rio De Janeiro)	+(55)-2139581449		Portuguese
CHEMTREC Cayman Islands	+(1)-345-749-8392		English
CHEMTREC Chile (Santiago)	+(56)-225814934		Latin American Spanish
CHEMTREC Colombia *		01800-710-2151	Latin American Spanish
CHEMTREC Costa Rica*	+(506)-40003869		Latin American Spanish
CHEMTREC Mexico*		01-800-681-9531	Latin American Spanish
CHEMTREC Panama	+(507)-8322475		Latin American Spanish
CHEMTREC Peru (Lima)	+(51)-17071295		Latin American Spanish
CHEMTREC Trinidad and Tobago*	+(1)-868-224-5716		English

Conforms to OSHA CFR 29 1910.1200 and aligns to the United Nations Globally Harmonized System Conforms to The United Nations Regulation Globally Harmonized System Revision 7

16.3 CHEMTREC in country emergency dial numbers continued:

MIDDLE EAST					
CHEMTREC Bahrain (Bahrain)	+(973)-16199372	**	Arabic		
CHEMTREC Israel (Tel Aviv)	+(972)-37630639		Hebrew		
CHEMTREC Saudi Arabia*	+(966)-8111095861		Arabic and English		
CHEMTREC Kuwait National	+965-22274681		Arabic and English		
	SUB SAHARAN A	FRICA			
CHEMTREC South Africa*		0-800-983-611	English		
	EAST ASIA	7			
CHEMTREC Hong Kong (Hong Kong)*		800-968-793	Cantonese		
CHEMTREC Japan (Tokyo)	+(81)-345209637		Japanese		
CHEMTREC South Korea*		00-308-13-2549	Korean		
CHEMTREC South Korea	+(82) 070-7686-0086		Korean		
CHEMTREC Taiwan*		00801-14-8954	Mandarin		
	SOUTHEAST A	SIA	*		
CHEMTREC Indonesia*		001-803-017-9114	Indonesian		
CHEMTREC Malaysia *		1-800-815-308	Malay		
CHEMTREC Malaysia (Kuala Lumpur)	+(60)-327884561		Malay		
CHEMTREC Philippines *		1-800-1-116-1020	Tagalog		
CHEMTREC Philippines (Manila)	+(63) 2-395-3308		Tagalog		
CHEMTREC Singapore*		800-101-2201	English and Mandarin		
CHEMTREC Singapore	+(65)-31581349		English and Mandarin		
CHEMTREC Thailand *		001-800-13-203-9987	Thai		
CHEMTREC Vietnam (Hanoi)*	+(84)-444581938		Vietnamese		
	SOUTH ASIA	C.			
CHEMTREC Bangladesh††	N/A	N/A	Bengali		
CHEMTREC India *		000-800-100-7141	Hindi		
AUSTRALIA & OCEANIA					
CHEMTREC Australia (Sydney)	+(61)-290372994		English		
CHEMTREC New Zealand	./(54) 00010034		En alliab		
(Auckland)*	+(64)-98010034		English		
*Phone numbers for countries marked with an asterisk must be dialed within the country					
*Phone numbers for countries marked with an asterisk must be dialed within the country. †† Phone numbers marked with a double dagger have a DID and greeting ONLY supplied by CHEMTREC					

16.4 SDS Preparation Date 11/15/2016

SDS Previous Issue Date: None

SDS Revision Date: 08/04/2018 Revised Sections 1,2,3,4,5,8,9,11,12,14,15,16

Prepared by SJC Compliance Education, Inc

16516 El Camino Real Suite 417

Houston, TX 77062 VP@sjcedu.org

